



*"Specializing In Well Stimulation Products"*

## **MS-200**

### Surface Tension Reducer

**MS-200** is designed and formulated to enhance the recovery of stimulation fluids by reducing surface tension and aiding in the clean-up of water based frac fluids and acidizing fluids.

**MS-200** is a non-ionic/anionic fluid that is very versatile and compatible with many of the various stimulation fluids used in the oil and gas industry. It is used in fracturing fluids as well as hydrochloric acid with little to no degradation to product after exposure to heat and extreme cold.

**MS-200** delivers superior water wetting characteristics in both carbonate and sandstone reservoirs. The result is a more efficient stimulation, with residual wetting, that enhances the performance and life of an oil or gas well and its longevity.

**MS-200** is used as a non-acidic breakdown fluid to enhance stimulation performance at a loading of .5 to 2 gpt.

<b>Specific Gravity:</b>	0.95-1.05
<b>Appearance/Odor:</b>	Clear to Amber/ Pleasant
<b>pH:</b>	6.0-8.0

**See SDS**

**MS-200** is recommended at a loading of .5 to 2 gpt in fracturing fluids and acidizing fluids. It is suggested to always run a compatibility of fluids.

**MS-200** is available in 55 gallon drums, 275 and 330 gallon totes.